



# Simulation of Networked ECUs for Drivability Calibration

Simulation of Networked ECUs for Drivability Calibration

10/10/10

D  
 . D  
 in  
 ( C ) in in  
 in u in in  
 in in u in in in  
 in u in in in  
 in in in C ,  
 in in in u in

u u  
h . h h  
I h u h  
( u h 100 %  
u ) h

u  
-

D , h u h  
EC u u .B h  
h ,  
u u u .  
h u h  
u u , h  
CC ,  
u h R OS ( -  
) h u .  
B , u h -  
CAN- -  
u h  
h R OS ,  
h u (Q  
s , 2). h , h C  
C u PC h u -  
h . h u -  
u u -  
(  
, 2.- u . -)  
h CAN, u -

hu    h h    u    -

h u u h SL- u  
u  
h . h h  
SL- u u h -

FIGURE 5

h u u h u u  
h u u u h h  
u h h  
u . h h 2  
( h ) h h h  
u . h u  
h h u u  
h h u u  
u  
( u ) u ( u h  
h u u ).  
I h 3 ( ) 4 ( h ) h  
u u u h  
h h u u -  
. I h h u h  
u , u  
u h h u h  
h u u h h -  
. u u h -  
u h .

h u h S , FIGURE 6  
h , h h h